

New!

MB-608 Ver.2

MB-608, threaded external bottom bracket for $\Phi 24\text{mm}$ through axle, has been upgraded to Ver. 2, further improved in its rotation and waterproof performance, and more serviceable!




**MB-608 (BSA)
STEEL Ver.2**

**MB-608 (BSA)
SUPER CERAMIC Ver.2**

Gasket-ring **New!**

The gasket rings provide secure fitting and keep water out of the frame. No thread locking agents (such as Lock Tight) are required. BB can easily be installed, removed and reused without fitting degradation, making the BB shell ideal maintenance hatch for internal cables.

Perfect fit



**Prevent creaking,
loosening & water ingress**



MB-608 ver.2
Gasket-ring set

Seal system

The waterproof & dustproof performance is further ensured by the sophisticated super-low friction seal system while realizing even smoother rotation, which is completely unique.

WATER PROOF DESIGN


Due to special seal system, the bearings don't require internal maintenance. Thus, disassembling the bearing is not necessary.

⚠ Don't disassemble : Never remove the plastic cover. If the seal is tampered with, it can never be repacked. This will result in permanent failure and void the warranty.

**Apply chain lube on the lip of the plastic cover (outer periphery) periodically. Wipe off dirt, apply a low viscosity chain lube.*

Cup design

The cups were downsized, become lighter and look more stylish.



Former model




MB-608 (BSA) SUPER CERAMIC Ver.2 MB-608 (BSA) STEEL Ver.2

- 1 BSA
- 2 BC1.37x24T
- 3 68mm
- 4 External BB tool

Crank compatibility

$\Phi 24\text{mm}$ through axle

- SUGINO : IDS24
- Shimano : HOLLOWTECH II



TL-PWS
BB wrench set

